


## Dimensions




A	B	C	D	E
7.1±0.5 mm	6.6±0.3 mm	3.0±0.3 mm	2.0Max. mm	1.6±0.3 mm

## Product Marking

Product Marking	R68 (Inductance Code)
-----------------	-----------------------

## Schematic Drawing



Equivalent Circuit

## Electrical Properties

Properties		Value	Unit	Tol.	Test Conditions
Inductance	L	0.68	μH	±20%	100KHz 1.0V
Heat Rating Current	I <sub>rms</sub>	7.5	A	Typ.	
Saturation Current	I <sub>sat</sub>	14.0	A	Typ.	L 14.0A drop 30% MAX. @ 100KHz/1.0V
DC Resistance	R <sub>DC</sub>	10.0	mΩ	Typ.	
DC Resistance	R <sub>DC</sub>	12.7	mΩ	Max	

Operating temperature range: -45 to + 125 °C


Storage condition:

Temperature Range: 0°C ~ 35°C; -40°C ~ 105°C (after PCB)

Humidity Range: 50% ~ 70% RH

Packaging: Taping : 2000 Piece/reel

## Recommended land pattern



<b>G</b>	2.40 mm (REF)
<b>H</b>	3.50 mm (REF)
<b>I</b>	2.70 mm (REF)